




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47B 39/00	A1	(11) International Publication Number: WO 99/04670 (43) International Publication Date: 4 February 1999 (04.02.99)
(21) International Application Number: PCT/IL98/00328 (22) International Filing Date: 13 July 1998 (13.07.98) (30) Priority Data: 121410 28 July 1997 (28.07.97) IL (71)(72) Applicant and Inventor: BARU, Eran [IL/IL]; Alkalai Street 3, 62742 Tel Aviv (IL). (74) Agent: ELIEZRI, Zohar, Avital, Dromi & Co., Taas Street 4, 52512 Ramat-Gan (IL).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: COMPUTER WORK STATION**(57) Abstract**

There is thus provided, according to the present invention, a computer work station including a user's seat (24) and a monitor supporting tray (52) positioned in front of the seat, comprising a first chassis unit (12) having a first base (16), an elongated seat supporting member (18), and first varying means (34) for varying the location of the seat along the seat supporting member between a relatively reclining position and a relatively upright position, a second chassis unit (14) having a second base (16), an elongated monitor supporting member (44, 48), and second varying means (64) for varying the location of the monitor supporting tray between an uppermost position and a lowermost position, and coupling means for coupling the seat to monitor supporting tray so that displacement of the seat toward the relatively reclining position results in the displacement of the monitor supporting tray toward the uppermost position, and displacement of the seat toward the relatively upright position results in the displacement of the monitor supporting tray toward the lowermost position.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COMPUTER WORK STATION

TECHNICAL FIELD

The present invention refers to computers in general, and to work stations therefor, in particular.

BACKGROUND ART

In recent years more and more people spend an increasing amount of time in front of computers, either professionally or as Internet users. In order to meet the needs of this growing market, extensive thought has been given to devise convenient, space-saving stations or centers that will make user's position in front of the computer more comfortable and less tiresome. Such prior art is disclosed, for instance, in US Patent No. 4,915,450 and the references cited therein. These work station systems were, however, designed primarily for professional users, at offices, rather than for domestic environments.

It is thus the major object of the present invention to provide a low-cost, furniture-piece like, modular computer work station, that will present the required features mainly for the benefit of the users.

DISCLOSURE OF THE INVENTION

There is thus provided, according to the invention present, a computer work station including a user's seat and a monitor supporting tray positioned in front of the seat, comprising a first chassis unit having a first base, an elongated seat supporting

member, and first varying means for varying the location of the seat along the seat supporting member between a relatively reclining position and a relatively upright position, a second chassis unit having a second base, an elongated monitor supporting member, and second varying means for varying the location of the monitor supporting tray between an uppermost position and a lowermost position, and coupling means for coupling the seat to the monitor supporting tray so that displacement of the seat toward the relatively reclining position results in the displacement of the monitor supporting tray toward the uppermost position, and displacement of the seat toward the relatively upright position results in the displacement of the monitor supporting tray toward the lowermost position.

BRIEF DESCRIPTION OF THE DRAWINGS

These and additional features of the invention will become more clearly understood in the light of the ensuing description of a preferred embodiment thereof given by way of example only with reference to the accompanying drawings, wherein:

Figure 1 is a front three-dimensional schematic representation of the work station according to a preferred embodiment of the invention;

Figure 2 is a rear three-dimensional schematic representation of Figure 1;

Figure 3 is a side view of the work station of Figure 1 and 2;

Figure 4 is a front view of Figure 3;

Figure 5 is a rear view of Figure 4;

Figure 6 shows a detail of construction of the work station of Figure 1; and

Figure 7 is another detail of construction of the computer work station of Figure 1.

BEST MODE FOR CARRYING OUT THE INVENTION

The computer work station generally denoted 10 essentially comprises two main assemblies: the seat carrying or supporting chassis or structure assembly generally denoted 12 and the monitor supporting structure generally denoted 14.

In the exemplified embodiment, assembly 12 comprises a base 16 carrying a pair of arcuate rails 18 and 20 extending generally in the direction of assembly 14 and connected thereto by a connector member 22. Preferably, the connection is of the quick dismantling type of any known design (not shown), for enabling the dismantling of the system into a kit form. The rails in the present example consist of tubular rods extending parallel to each other. A seat denoted 24 is slideable on rails 18 and 20 by being mounted on a carriage comprised of brackets 26 and 28, each formed with a pair of complementary openings through which arcuate rails 18 and 20 extend. This will allow the guided sliding movement of the seat, with an associated keyboard tray 29, up and down along the arcuate path. A pair of foot pedals 30 and 32 are provided on which the user's feet can rest and which are useful to apply, whenever requested, the force for pushing the seat away down the rails 18 and 20.

The seat carriage is coupled to a cable 34 wound around an idler roller 36 and passes through a tubular guiding member 38 connected at its one end to base 16 by a coupling comprising a coil spring 39 for a purpose to be explained further below. The other end of member 38 is releasably received by a bracket 40, mounted to monitor supporting structure 14.

Structure 14 comprises a base 42 and a pair of tubular, guide rails or rods 44 and 48. Rods 44 and 48 are again arcuate, extending parallel to each other, and - besides supporting the brackets 22 and 40 as aforesaid - carry a third bracket 50 being

part of the monitor tray assembly designated 52. Monitor support tray 54 is free to slide on rails 44, 48 by being provided with a pair of openings 56 and 58 (see Fig. 7) as well as auxiliary rollers 60 and 62. Monitor support tray 54 is held in suspension or floating state against a compression coil spring 64, situated between bracket 50 and the bottom surface of monitor support tray 54 and thus is moveable downwards when pulled by cable 34 against spring 64 to change its location along rails 44 and 48, i.e., upon moving seat 24 toward the less reclining direction.

As seen, in Figure 1-5, cable 34 emerges from tubular guiding member 38, and extends upwards through brackets 22 and 50, and may be connected, by any means provided for this purpose - such as a hook 66, at the bottom side of monitor support tray 54.

It will be further now indicated, with specific reference to Fig. 6, that tubular guiding member 38 through which cable 34 extends, is somewhat resiliently sustained by base 16, by means of spring 39, with cap 70 and pivot 72 on the one hand, and a tie rod 74 on the other hand, thus allowing an additional degree of freedom which is important to facilitate the assembly process of the work station 10 as a whole.

As will be now readily understood, the user sitting on seat 24 is able, by stretching his legs against pedals 30 and 32, to push seat 24 backwards, thereby relieving the initial pulling force applied to monitor support tray 54 and causing it to rise by sliding along rails 44 and 48 under the bias of the spring 64. Contrarily, when the user wants to revert from a reclining position into a more upright position, by sliding his seat forwards, the monitor and monitor support tray 54 will descend under the compression of spring 64 to a lower location, thereby adjusting the position of the display screen relative to his eyes.

Therefore, the arrangement as shown lends itself to various ergonomically different positions within certain predetermined limit, so that the user can exercise any position without having to stand up and apply adjustments to various other components of the work station.


It will be also noted that the construction of the computer work station is extremely simple, low-cost, can be supplied in kit-form to consumer, thereby still lowering the marketing price of the work station.

Various additional features will be readily apprehended, bearing in mind that modification or variation of the exemplified embodiment shall be deemed to be included within the scope of the invention and defined in and by the appended claims.

CLAIMS

1. A computer work station including a user's seat and a monitor supporting tray positioned in front of the seat, comprising:
 - (a) a first chassis unit having a first base, an elongated seat supporting member, and first varying means for varying the location of the seat along said seat supporting member between a relatively reclining position and a relatively upright position;
 - (b) a second chassis unit having a second base, an elongated monitor supporting member, and second varying means for varying the location of said monitor tray supporting between an uppermost position and a lowermost position; and
 - (c) coupling means for coupling the seat to said monitor supporting tray so that displacement of the seat toward said relatively reclining position results in the displacement of the monitor supporting tray toward said uppermost position, and displacement of the seat toward said relatively upright position results in the displacement of the monitor supporting tray toward said lowermost position.
2. The computer work station of Claim 1, wherein said first chassis unit comprises a pair of parallel, arcuate rails, and the seat is mounted to a carriage on the rails.

3. The computer work station of Claim 2, wherein said second chassis unit comprises a pair of parallel arcuate rails slidably supporting said monitor supporting tray.
4. The computer work station of Claim 3, wherein said monitor supporting tray is supported by a compression spring resting against a bracket affixed to said rails below said monitor supporting tray.
5. The computer work station of Claim 4, wherein said coupling means comprise a cable connecting between said carriage and said monitor supporting tray.
6. The computer work station of Claim 5, wherein said cable extends through a tubular guiding member mounted between said first base and said second base.
7. The computer work station of Claim 5, wherein said cable is wound around an idler roller.
8. The computer work station of Claim 7, wherein said idler roller is mounted onto a resilient console.
9. The computer work station of Claim 3, wherein said monitor supporting tray is provided with a pair of auxiliary rollers engaging, respectively, said pair of parallel arcuate rails.
10. The computer work station substantially as hereinbefore claimed and described with reference to the accompanying drawings.



2/5




FIG. 2

3/5






FIG. 3



5/5




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IL98/00328

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A47B 39/00

US CL :297/174

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 297/174,170,172,344.1.

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,779,922 A (COOPER) 25 October 1988, (25/10/88), see entire document.	1
X	US 4,915,450 A (COOPER) 10 April 1990 (10/04/90), see Figures 1 and 2.	1
A	US 4,046,419 A (SCHMITT) 06 September 1977 (06/09/77) see entire document.	1

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

B earlier document published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

A

document member of the same patent family

Date of the actual completion of the international search

20 OCTOBER 1998

Date of mailing of the international search report

17 NOV 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ANTHONY BARFIELD

Telephone No. (703) 308-2168